



► INSTALLATION REIHENSCHALTUNG



CODE	MODELL	ANZ. PROJ.	MAXIMALE KABELLÄNGE (METER)					
			2x1,5mm ²	2x2,5mm ²	2x4mm ²	2x6mm ²	2x10mm ²	2x16mm ²
56001	LumiPlus PAR56 V1 AC RGB lamp	1	7	14	22	33	56	90
59126	LumiPlus PAR56 V1 AC RGB Wireless lamp	2	3	6	11	16	28	45
71205	LumiPlus Flexi V1 AC RGB wireless	3	-	4	7	11	18	30
71203	LumiPlus Flexi V1 AC RGB	4	-	3	5	8	14	22
52596	LumiPlus PAR56 V1 AC W lamp	1	16	33	54	81	135	216
71200	LumiPlus Flexi V1 AC W	2	8	16	25	38	65	104
71212	LumiPlus FlexiNiche V1 AC W	3	5	10	17	26	43	70
71214	LumiPlus FlexiSLIM V1 AC W	4	3	7	11	17	29	47
71216	LumiPlus FlexiRapid V1 AC W	4	3	7	11	17	29	47
67515	LumiPlus PAR56 V1 DC W lamp	1	65	135	215	320	530	870
71201	LumiPlus Flexi V1 DC W	2	34	68	109	163	272	435
71213	LumiPlus FlexiNiche V1 DC W	3	22	45	72	108	180	289
71215	LumiPlus FlexiSLIM V1 DC W	4	17	34	54	82	137	219
71217	LumiPlus FlexiRapid V1 DC W	4	17	34	54	82	137	219
43411	LumiPlus PAR56 V2 AC RGB lamp	1	3	7	11	17	29	47
45637	LumiPlus PAR56 V2 AC RGB DMX lamp	2	-	3	5	8	14	23
		3	-	-	3	5	9	15
		4	-	-	-	4	7	12
67516	LumiPlus PAR56 V2 DC W lamp	1	27	55	90	140	240	380
71202	LumiPlus Flexi V2 DC W	2	15	30	48	72	121	193
		3	9	19	31	47	78	126
		4	7	14	23	35	59	95
71233	LumiPlus Flexi V2 AC W	1	7	14	23	35	58	93
		2	3	7	11	17	29	47
		3	-	5	8	13	21	35
		4	-	3	5	8	14	23
71204	LumiPlus Flexi V2 AC RGB	1	3	8	13	20	33	58
71208	LumiPlus Flexi V2 AC RGB DMX	2	-	4	7	11	19	31
59803-59801	LumiPlus Design RGB	3	-	-	4	7	12	20
59811-59809	LumiPlus Design RGB DMX	4	-	-	3	5	9	15
59807-59805	LumiPlus Design W	4	-	-	3	5	9	15

► INSTALLATION REIHENSCHALTUNG



CODE	MODELL	ANZ. PROJ.	MAXIMALE KABELLÄNGE (METER)					
			2x1,5mm ²	2x2,5mm ²	2x4mm ²	2x6mm ²	2x10mm ²	2x16mm ²
52124 - 52125 52126 - 52127 52128 - 52129 52130 - 52131 52132 - 52133 52134 - 52135 52136 - 52137 52138 - 52139 52140 - 52141	LumiPlus Mini V2	1	34	68	109	162	272	435
2		17	34	54	82	137	219	
3		11	22	36	54	90	144	
4		8	17	27	41	68	109	
59971 - 59972 59973 - 59974 59975 - 59976 59977 - 59978 59979 - 59980 59981 - 59982 69633 - 69634 69635 - 69636 69637 - 69638	LumiPlus Mini V3	1	34	68	109	162	272	435
2		17	34	54	82	137	219	
3		11	22	36	54	90	144	
4		8	17	27	41	68	109	
38814 - 38816 40765 - 40766 64552 - 64553 64554 - 64555 64557 - 64558 64559 - 64560	LumiPlus Micro	1	34	68	109	162	272	435
2		17	34	54	82	137	219	
3		11	22	36	54	90	144	
4		8	17	27	41	68	109	

Die berechneten Querschnitte entsprechen den Normen IEC 60287-1-3:2002